



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Spun LED Pendant SPP Series

Features

Hand-blown glass with white pattern molten glass cane. Pendant is suspended with an 9 foot adjustable cord and can be ordered individual or with a multi-point canopy. Canopy mounts to a standard junction box (not included).

Construction

The glass cylinder is 16-3/4" tall and 5" in diameter and held together into place by three decorative studs. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

Finish

The canopy is plated in Satin Nickel.

Diffuser

Glass cylinder pendant is .40" thick. Glass colors include clear (CL), smoke (SM) and steel blue (SB).

Electrical

D1 Driver

Direct wired with a constant current low voltage electronic LED driver rated at 120 VAC. The driver is dimmable with a 2-wire (Triac) or electronic low voltage (ELV) dimmer switch.

D2 Driver

Direct wired with a constant current low voltage electronic LED driver rated for 120-277 VAC. LED driver is dimmable 0-10V DC.

Lamping

All pendants include a 10W LED module. Light engine produces 1000 source lumens. 3000K and 4000K (CCT). 50,000 hr. LED life, 90 CRI.

Certification

All fixtures are ETL listed for damp locations.

Specifications and dimensions

subject to change without notice.



Ordering Information:

5" DIA. x 16-3/4" H

Series	Source Lumens	LED	CCT	Driver	Finish	Glass	Canopy Options
SPP	1000	L	30 3000K 40 4000K	D1 Voltage (120V TRIAC Dimming) D2 Voltage (120-277V 0-10V Dimming)	SN Satin Nickel	CL Clear SM Smoke SB Steel Blue	Blank Monopoint LNR3 (3) Light Linear RND3 (3) Light Round RND6 (6) Light Round

Example: SPP1000L30D2SNSMLNR3