Brim Head LED T20





DESCRIPTION

The Brim head and display light by Tech Lighting features a handsome and industrial design while delivering on functionality. The ultra-slim head features field-changeable optics and an optional decorative glass collar. The latest advances in technology deliver an extremely powerful LED head without the bulk typically needed to conceal a driver and manage thermal performance. The Brim head is highly customizable and is compatible with the Monorail and Monopoint systems by Tech Lighting. This low-voltage display head is ideal for commercial and residential lighting applications. The Brim ships with an integrated lens holder to accommodate two dimmable lenses or louvers (both sold separately). Includes 7 watt, 855 delivered lumens, 2700K or 3000K field replaceable LED module Dimmable with most LED compatible ELV and Triac dimmers. Choice of 20°, 30° or 40° field changeable optics. Integrated lens holder accommodates up to 2 lenses or louvers (sold separately) As a general rule when using the Brim head, we do not recommend using greater than 33% of the maximum wattage specified for the low voltage transformer due to inrush current requirements. For assistance in calculations, please contact Technical Support.

INSTALLATION

Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system. For use on T~TRAK, order FreeJack version and T~TRAK FreeJack Connector (sold separately).

WEIGHT

 $0.23lb / 0.1kg \pm$











(A)

1.3"

33 mm

76 mm

black finish

transparent smoke black finish

clear

transparent smoke satin nickel finish satin nickel finish

ORDERING INFORMATION

| 700 SYSTEM BRM | COLOR TEMP | BEAM SPREAD | LENGTH (A) | COLOR | FINISH |
|---|--------------------------------------|----------------------------|---|-----------------------------|---------------------------------|
| FJ FREEJACK MP MONOPOINT MO MONORAIL MO2 TWO-CIRCUIT MONORAIL | 927 90 CRI 2700K 930 90 CRI 3000K | 20 20° 30 30° 40 40° | 05 5" 08 7.76" 14 13.76" | C CLEAR K TRANSPARENT SMOKE | B MATTE BLACK S SATIN NICKEL |

Note: MP includes 4 Round Flush Canopy.

When installing LED option on MO2 only magnetic transformers may be used.



7400 Linder Avenue Skokie, Illinois 60077

T 847.410.4400 F 847.410.4500

Tech Lighting, L.L.C.

| 700 BRM | | | | |
|----------------------------------|--|--|--|--|
| FIXTURE TYPE: JOB NAME: NOTES: | | | | |
| | | | | |

