

Project:

# Light Frames Downlight LED Sconce Spec Sheet

SKU: 7200.74-WL Learn more at: https://sonnemanlight.com/light-frames-downlight-led-sconce

Description: LED illumination is directed downward from the interior top edge of the frame within a broad rectilinear column. Also available as a <u>Bollard</u> and <u>Up/Down LED Sconce</u>.

Type #:

#### Dimensions

Height:	13"
Width:	7"
Extends:	2.5"
Minimum Extension:	2.5"
Maximum Extension:	2.5"
Canopy/Backplate/Base Depth:	6.5
Canopy/Backplate/Base Height:	4.5

### **Electrical Specs**

Bulb(s) Included?:
Bulb 1 Type:
Input Voltage:
Wattage:
Initial Lumens:
Delivered Lumens:
Color Temperature:
CRI:
Power Supply Type:
Power Supply Quantity:
Power Supply Location:
Dimming Type:
Bulb Max Wattage:

#### Yes Integral LED 120VAC 14 1820 640 3000K 90 Driver 1 Outlet Box TRIAC/ELV 14

## Installation

#### Installation:

Installation Orientation:

#### Shipping

Carton 1 L x W x H: Carton 1 Gross Weight: Fixture Weight:

#### Shade

Shade 1 Material:

### Aluminum

Licensed electrician

required

Vertical

15" X 9" X 5"

5 LBS


4

#### **Available Finishes**

Available Finishes: Textured Bronze (.72), Textured Gray (.74), Textured White (.98)







#### **General Listings**

Dark Sky Friendly:

41/3

Features: Certification: Color/Finish: Wet Rated C-ETL-US Textured Gray (.74) N