



Features

- · Line voltage no drivers needed
- Interconnectable kits (3000K Warm White and 6400K Cool White)
- LED Flexbrite consumes only 1 watt per foot
- Dimmable 5-100%*
- UL Listed[†] for indoor and outdoor use
- 60,000 hours rated life

Available CCT





3000K

6400K

Dimming Options

- ELV (5-100%*)
- LED (5-100%*)
- CL (5-100%*)

Listing / Ratings⁺



LED Flexbrite Kits

Easy to use flexible, dimmable, and economical LED rope light has UV inhibitor built into the PVC housing for use outdoors. Save 73% in running costs compared to incandescent rope light. LED Flexbrite last up to three times as long as incandescent rope.

Technical Information

Series	LR-LED (Kits)			
Input Voltage	120V AC, 60Hz			
CCT	3000K (WW) / 6400K (CW)			
CRI	67+ (UWW) / 72+ (WW) / 75+ (WH)			
Wattage	1W per ft			
Lumens	See individual product			
Max Run	192 feet (kits)			
Cuttable	N/A [†]			
IP Rating	IP65** (uncut), void if cut			
Dimmable	5-100%*			
Rating	UL Listed [†] for indoor/outdoor use			
Rated Life	60,000 hrs			

^{*}Minimum loads may apply. Per the NEC, switched wall outlets cannot be used with

^{**}IP65 rated only when used with pre-attached molded power cord and end cap is either pre-attached or properly sealed with dielectric grease, silicone and shrink

[†]UL Listing is void if product is cut







Warm White Kits 120V / 3000K / 72CRI / 32Lm/ft / 1/2" Diameter

Cool White Kits 120V / 6400K / 75CRI / 34Lm/ft / 1/2" Diameter

FLEXBRITE ORDERING INFORMATION			*Cu	*Custom Cut Orders - Please Allow Up To 2-4 Weeks Order Processing & Delivery*			
ITEM NUMBER	ССТ	LENGTH	LUMENS / FT	WATTAGE	IP RATING	CRI	CUTTING
LR-LED-WW-3	3000K	3 ft	32Lm / ft	3W	IP65	67+	N/A
LR-LED-WW-9	3000K	9 ft	32Lm / ft	9W	IP65	67+	N/A
LR-LED-WW-15	3000K	15 ft	32Lm / ft	15W	IP65	67+	N/A
LR-LED-WW-30	3000K	30 ft	32Lm / ft	30W	IP65	67+	N/A
LR-LED-WW-75	3000K	75 ft	32Lm / ft	75W	IP65	67+	N/A
LR-LED-CW-3	6400K	3 ft	34Lm / ft	3W	IP65	75+	N/A
LR-LED-CW-9	6400K	9 ft	34Lm / ft	9W	IP65	75+	N/A
LR-LED-CW-15	6400K	15 ft	34Lm / ft	15W	IP65	75+	N/A
LR-LED-CW-30	6400K	30 ft	34Lm / ft	30W	IP65	75+	N/A
LR-LED-CW-75	6400K	75 ft	34Lm / ft	75W	IP65	75+	N/A

120V Kits Include: (1) Removable 5ft power cord with 1.6A inverter, (1) removable end cap, and (1) mounting clip per foot of rope

FLEXBRITE ACCESSORIES				
ITEM NUMBER	DESCRIPTION			
LR-LED-EXT3	3' linking cable			
RL-TRACK-4	4' clear plastic mounting track			
RL-CLIP/SCREW	Clear plastic mounting clips (qty 10)			
LR-CLIP-20	Clear plastic mounting clips (qty 20)			





RL-TRACK-4

RL-CLIP/SCREW LR-CLIP-20