



METRO

SCONCES WALL



SPECIFICATIONS:

DESCRIPTION

Wall-mounted **ADA-compliant** sconce featuring open-top handcrafted glass and radiused canopy.

LAMPING

Standard: 60W B10 120V incandescent, suitable for dimming.

CFL: 18W 4-Pin CFL with non-dimming electronic ballast. 120V, lamp not included.

GU24 CFL: Self-ballasted GU24 lampholders. 18W max, 120V, lamp not included.

LED: 7W LED Replaceable source, 120V, non-dimmable, included.

DIFFUSER

Diffuser shall be handcrafted glass of Opal Matte decor. 2.375" Dia. x 10" H

CONSTRUCTION

Fixture utilizes solid brass arm assembly and stamped steel canopy (4.75" W x 12.0" H), with plated metal finish.

METAL FINISH


Fixture shall be finished in Bronze, Polished Nickel or Satin Nickel.

MOUNTING

Installs directly to a 4" octagonal outlet box. 75°C supply wire required for incandescent lamplighting. Top of glass is approximately 6" above the outlet box centerline.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



METRO SHOWN IN OPAL MATTE, POLISHED NICKEL (1WE-118607-PN)

OPAL MATTE, SATIN NICKEL

OPAL MATTE, BRONZE



ORDERING:

FIXTURE	DECOR	LAMP OPTIONS	METAL FINISH
1WE 1 Light	118607 Opal Matte	(blank) 60W B10 Incan E1 18W Quad 120V GU24* 18W Quad 120V LED 7W LED 120V, non-dimmable	BR Bronze PN Polished Nickel SN Satin Nickel

*Note the lamp must be Quad style to fit diffuser.

Ex. 1WE-118607-SN
Metro Wall Sconce w/ Opal Matte Glass, Satin Nickel Finish

Project Information:

LED SCONCES:

- Total power of only 7 watts
- Non-dimmable
- Rated life: 30,000 hours
- 700 lumens
- CCT: 3000° Kelvin
- CRI: 80+

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/14