


TWO-CIRCUIT MONORAIL

Two-Circuit MonoRail

DESCRIPTION

Low-voltage conductor of three individual conductive metal pieces fused together with plastic separators. Hand-bendable, field-cuttable Two-Circuit MonoRail is rated for 300 watts per circuit at 12 volts. Each piece of rail is shipped with conductive connectors to join rail pieces end to end. Order additional connectors if cutting and rejoining rails. Two-Circuit MonoRail bends horizontally to a radius as small as 12", and custom factory bends are available. It cannot be bent vertically in the field.



WEIGHT

0.42-1.65lb / 0.19-0.75kg ±

brown

COLOR OPTIONS



brown

clear

ORDERING INFORMATION

700MO2A SHAPE OR SIZE	LENGTH (A)	COLOR	FINISH
STRAIGHT	24 24" 48 48" 96 96"	BR BROWN CLEAR	Z ANTIQUE BRONZE C CHROME S SATIN NICKEL



TECH LIGHTING®

7400 Linder Avenue T 847.410.4400
Skokie, Illinois 60077 F 847.410.4500

Tech Lighting, L.L.C.

700MO2A _____
FIXTURE TYPE: _____
JOB NAME: _____
NOTES: _____



©2014 Tech Lighting, L.L.C. All Rights Reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.