



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Apex LED Overbed APB Series

Features

White patterned linen white or jute acrylic front panel provides a soft glow accent to this contemporary wall mount senior care overbed light. The Apex provides both ambient and task light with a four way pull switch, standard (120 volt only). Top diffuser and bottom diffuser are frosted white acrylic.

Construction

The light wiring channel is formed from 22-gauge steel. An internal divider provides separate lamp compartments for controlled up light and down light. Double laminated fabric material with solid wood trim. Fixture can mount horizontally only. Power connections can be made in the fixture wiring channel or in a standard junction box (not included).

Finish

Solid wood accent available in Espresso or Weathered Grey finish.

Diffuser

LumaFuse™ double laminated fabric/acrylic. 0.110" thick fabric is available in Jute or Linen White. Standard top and bottom diffuser.

Electrical

Input 120VAC / 60 Hz

Not compatible with dimmers. Integrated four position pull switch (on up, on down, on both, all off) and single pull switch for nightlight.

LED

Integrated LED modules capable of producing:

60W = 4050 source lumens

80W = 5400 source lumens

Rated for 50,000 hours, 3000K (CCT), 90 CRI.

Provides 50 footcandles of reading light over bed.

Certification

All fixtures are cETLus listed for indoor damp locations.

ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions
subject to change without notice.

Ordering Information:

Espresso/Jute	Weathered Grey/Jute	LED	Source Lumens	CCT	L	H	D
APB3940L30ENES-JT	APB3940L30ENWG-JT	60W	1350 up/2700 down	3000K	38"	4-3/8"	4"
APB5154L30ENES-JT	APB5154L30ENWG-JT	80W	1800 up/3600 down	3000K	50"	4-3/8"	4"

Espresso/ Linen White	Weathered Grey/ Linen White	LED	Source Lumens	CCT	L	H	D
APB3940L30ENES-LW	APB3940L30ENWG-LW	60W	1350 up/2700 down	3000K	38"	4-3/8"	4"
APB5154L30ENES-LW	APB5154L30ENWG-LW	80W	1800 up/3600 down	3000K	50"	4-3/8"	4"

