

Gemini LED Pendant GEMP Series

Features

This pendant features double rings with outer illumination. Includes adjustable cords, expandable up to 9 ft.

For use in kitchen, dining, foyers or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. This fixture mounts to a standard junction box (not included).

Construction

Extruded aluminum housing. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

Finish

Black, Gold or Painted Nickel finish.

Diffuser

White acrylic diffuser.

Electrical

Input 120-277 VAC 60 HZ. Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120 VAC.

I FD

Integrated LED modules capable of producing: 45W = 2200 delivered lumens 60W = 3000 delivered lumens Selectable 2700K, 3000K, 3500K, 4000K, 5000K (CCT). Rated for 50,000 Hrs., 90 CRI.


Certification

All fixtures are cETLus listed for indoor damp locations. Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 year from date of purchase.

Specifications and dimensions subject to change without notice.














Ordering Information:

Black	Gold	Painted Nickel	Lumens		Н	DIA
				2700K/3000K/3500K/4000K/5000K 2700K/3000K/3500K/4000K/5000K		