

Project:

Fixture Type: Location:

Contact:

Images:

Wall mounted • Wet location listed PROGRESS LED

energy STA

Description:

Wall Lantern

P560073-031-30

Z-1060 presents a functional design with a modern sensibility. Architectural style housing is diecast for added durability. The glass diffuser is secured without visible fasteners for an overall clean appearance. LED source delivers both energy efficiency and maintenance-free operation.

Specifications:

- Black (-031) (painted)
- Aluminum construction
- Clear Seeded Glass diffuser
- One light LED wall lantern
- One 9W LED module
- Features 3000K and warm white color, 90 CRI
- 624 lumens, 66 lumens per watt (source)
- A functional design with a modern sensibility
- Architectural style housing is die-cast for added durability
- The glass diffuser is secured without visible fasteners for an overall clean appearance
- \cdot $\,$ LED source delivers both energy efficiency and maintenance-free operation $\,$
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR[®] qualified
- Meets California Title 24 JA8-2016

Performance:

| Number of Modules | 1 | Depth Heigh |
|------------------------|-------------------------------------|----------------|
| Input Power | 9w | H/CTF |
| Input Voltage | 120 V | |
| Input Frequency | 60 Hz | Glass |
| Lumens/LPW (Source) | 624/66 (LM-82) | Width |
| Lumens/LPW (Delivered) | 346/36.8 (LM-79) | Heigh |
| ССТ | 3000 K | |
| CRI | 90 CRI | |
| Life (hours) | 60,000 (L70/TM-21) | |
| FCC | Meets FCC Title 47, Part 15 Class B | |
| Min. Start Temp | -30 °C | |
| Max. Operating Temp | 30°C | |
| Warranty | 5 year limited warranty | |
| Labels | cCSAus Wet location listed | |
| | ENERGY STAR [®] qualified | |
| | Meets California Title 24 JA8-2016 | |



Dimensions:

Width: 4-1/2" Depth: 4-3/4" Height: 4-1/2" H/CTR: 2-1/4"

Glass Width: 3-1/2" Height: 3-1/4"



Wall Lantern

Wall mounted • Wet location listed PROGRESS LED

P560073-031-30

nergy

Dimming Notes:

P560073 is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

| Lutron Diva DVELV-300P |
|----------------------------------|
| Lutron Nova T NTELV-300 |
| Lutron Caseta |
| Lutron Ariadni AY-600P |
| Leviton Illumatech IPI06-1LZ |
| Leviton SureSlide 6672 |
| Lutron Ariadni AYCL-153P |
| Lutron Skylark Contour CTCL-153P |
| Lutron Diva DVCL-153P |
| Lutron Toggler TGCL-153P |
| Lutron Maestro MACL-153M |
| Lutron Ariadni AYLV-600P |
| Lutron NOVA T NTLV-600 |
| lutron Maestro MAELV-600 |
| Lutron spacer/system SPSELV-600 |
| Lutron Renoir II AWRMG-EAW |
| Lutron Nova N-600 |
| |

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.