UL SPECIFICATION

135 [5 1/4"]

³⁶

3/4" 2 93

62 [2 1/2"]


- * FIXTURE SHALL BE LISTED FOR LOCATION ONLY AND LABELED AS SUCH.
- FIXTURE MUST BE MANUFACTURED IN ACCORDANCE WITH UL STANDARD 1598.

PARTS SPECIFICATIONS ITEM QTY DESCRIPTION

- (1) SOCKET- UL LISTED/CSA CERTIFIED BASE= MEDIUM SOCKET= PORCELIN SEE LEAD WIRE FOR SOCKET WIRE SPEC.
- LEAD WIRE- 120" В (1) FROM FRAME TOP UL LISTED/CSA CERTIFIED, AWG #18 105°C SPT-1 Black WIRE. STRIP 1/2 [12.7], SPLIT 3 [76.2]. FROM TOP OF SCROLL. (SEE CHART FOR COLOR).
- C (1)GROUND WIRE- 120" FROM FRAME TOP 1/4 LAY COPPER GROUND WIRE. FROM TOP OF SCROLL. (SEE CHART FOR TINT).

INNOVATIONS LIGHTING

DESIGN COPYRIGHT - 29/07/2020 ALL RIGHTS RESERVED AND MAY NOT BE DUPLICATED WITHOUT OUR WRITTEN PERMISSION



NOTICE: ANY DESIGN OR OTHER INFORMATION HEREON DEVELOPED BY THIS COMPANY IS CONFIDENTIAL MATERIAL AND EXCLUSIVE PROPERTY OF THE L.D. ALIYA CO. DISCLOSURE OR REPRODUCTION REQUIRES THE WRITTEN CONSENT OF THE L.D. ALIYA CO.



"mm" DIMENSION INDICATED IN [] DIMENSION IN [] IS FOR REF. ONLY DRAWN IN THIRD ANGLE TOLERANCES (EXCEPT AS NOTED) **PROJECTION** DECIMAL ANGULAR FRACTIONAL SCALE NONE ±.031 ± 1/2° ± 1/32 1:7 .X ±.015 DRAWN BY CHECKED BY DATE .XXX ±.005 3/31/2021

TITLE **1LT PENDANT**

REV. PART NO. **PENDANT** REV ITEM NO. 341-1S-BK (BK)