

Medium Wall Lantern

Project:

Fixture Type: Location:

Contact:

Images:

Wall mounted • Wet location listed PROGRESS LED



P6085-3130K9

LED wall lantern with etched white linen glass. Includes dark sky shield for full cut-off illumination or remove for a traditional lighting effect. 120V AC replaceable LED module, 1,211 lumens 71.2 lumens/ watt per module (source). 3000K color temperature and 90+ CRI.

Specifications:

Description:

- Black (-31) (powder coat paint)
- Aluminum Construction
- · Etched White Linen glass cylindrical diffuser
- LED Module is replaceable (part # 93053641)
- Etched white linen glass.
- · Includes removable dark sky shield for full cut-off illumination.
- Powder coated finish.
- 1,211 lumens 71.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR[®] qualified
- · Meets California Title 24 high efficacy requirements for outdoor use only

Performance:

		Diffici
Number of Modules	1	Width: Depth: Height: H/CTR:
Input Power	17w	
Input Voltage	120 V	
Input Frequency	60 Hz	
Lumens/LPW (Source)	1211/71.2 (LM-82)	
Lumens/LPW (Delivered)	234/14.1 (LM-79)	Glass Width: <u>9</u> Height:
ССТ	3000 K	
CRI	90 CRI	
Life (hours)	60,000 (L70/TM-21)	
FCC	Meets FCC Title 47, Part 15 Class B	
Min. Start Temp	-30 °C	
Max. Operating Temp	30 ℃	
Warranty	5 year warranty	
Labels	cCSAus Wet location listed	
	ENERGY STAR [®] qualified	
	Meets California Title 24 high efficacy requirements	
	for outdoor use only	



Dimensions:

Width: 9" Depth: 10-1/2" Height: 12-1/2" H/CTR: 3-1/8"

Glass Width: 5-5/16" Height: 7-3/8"



Medium Wall Lantern

Wall mounted • Wet location listed PROGRESS LED



P6085-3130K9

Dimming Notes:

P6085 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.