

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Frame

Pendant 3000K

Model & Size	Color Temp & CRI	Finish	Watt	LED Lumens	Delivered Lumens	Title 24
PD-29828 28"	3000K 90	AL Brushed Aluminum	55W	6334	5131	Yes
	3000K 90	BK Black	55W	6334	5131	Yes

Example: **PD-29828-AL**

DESCRIPTION

An extruded acrylic diffuser with mitered edges gives this design a clean, elevated look, evenly spreading the powerful LED light for a geometric illumination that matches back to the rectilinear canopy.

FEATURES

- Thin color matched powered aircraft cables and hardware
- Crisp mitered joints
- Can be mounted on a sloped ceiling
- Driver concealed within the canopy
- 5 year warranty

SPECIFICATIONS


Color Temp:	3000K
Input:	120-277 VAC, 50/60Hz
CRI:	90
Dimming:	ELV: 100 - 10%, 0-10V: 100 - 3%
Rated Life:	50000 Hours
Mounting:	Heavy gauge retention clips support trim firmly. Safety cabling standard.
Standards:	ETL, cETL, Title 24 JA8-2016 Compliant Damp Location Listed
Construction:	Aluminum body with extruded acrylic diffuser



FINISHES



LINE DRAWING



Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Frame

Pendant 3000K

Model & Size	Color Temp & CRI	Finish	Watt	LED Lumens	Delivered Lumens	Title 24
PD-29858 58"	3000K 90	AL Brushed Aluminum	58W	7160	5800	Yes
	3000K 90	BK Black	58W	7160	5800	Yes

Example: **PD-29858-AL**

DESCRIPTION

An extruded acrylic diffuser with mitered edges gives this design a clean, elevated look, evenly spreading the powerful LED light for a geometric illumination that matches back to the rectilinear canopy.

FEATURES

- Thin color matched powered aircraft cables and hardware
- Crisp mitered joints
- Can be mounted on a sloped ceiling
- Driver concealed within the canopy
- 5 year warranty

SPECIFICATIONS

Color Temp:	3000K
Input:	120-277 VAC, 50/60Hz
CRI:	90
Dimming:	ELV: 100 - 10%, 0-10V: 100 - 3%
Rated Life:	50000 Hours
Mounting:	Heavy gauge retention clips support trim firmly. Safety cabling standard.
Standards:	ETL, cETL, Title 24 JA8-2016 Compliant Damp Location Listed
Construction:	Aluminum body with extruded acrylic diffuser



FINISHES



LINE DRAWING

