P20LED203-6PK

CRI 80 5000K 550Lumens LED Reflector



ø63

The high performance LED PAR bulb.

Perfect for track and recessed light fixtures.

For commercial or home lighting applications

Easy to use - designed in traditional bulb shapes and fits easily into existing fixtures

Performance

- LED PAR bulb is designed to provide 25000 hours of life
- Energy-saving & Super bright, saving 85% energy compared with traditional halogen lamp
- UL & ES compliant.

Construction

- Rotary Extrusion Aluminum for excellent heat dissipation
- Dimmable.


Installation

- Rated for indoor/outdoor use
- Suitable for damp/wet locations.

Individual Box Height (Inch)

Individual Box Weight Per Unit (Lbs)

- Can't be used in totally enclosed fixtures
- Not for use with emergency exit fixtures or emergency exit lights
- Size:Φ2.48"(63mm)*H3.35"(85mm)



80

Specifications

Category	Light Bulb	Inner Package Length (Inch)	8.27
Bulb Shape	PAR20	Inner Package Width (Inch)	5.7
Bulb Base Type	E26	Inner Package Height (Inch)	3.94
Bulb Base Finish	Chrome	Inner Package Weight Per Unit (Lbs)	1.79
Color Temperature	5000K	Inner Package Quantity	6
Beam Angle	40°		
Finish	Silver		
CRI	80		
Average Life (Hours)	25000		
Estimated Yearly Energy Cost (11 ¢/Kwh)	0.84		
Life Based On 3Hrs/Day (Years)	22.83	Lamp Type	PAR20
Product Length (Inch)	N/A	Dry/Wet/Damp	Wet
Product Width (Inch)	2.48	Energy Star	YES
Product Height (Inch)	3.15	Power Factor	>0.9
Product Extension (Inch)	N/A	Current	80mA
Product Weight Per Unit (Lbs)	0.22	Lumen/Watt	79
Dimmable	YES	Warranty (Year)	3
Watts	7W	DLC (Yes/No)	No
Watt Equivalent	50W	Input Voltage	120V
Lumens	550	Housing Material	Aluminum
Certification (UL/ETL/FCC)	UL	Lens	Plastic
Individual Box Length (Inch)	2.64	Led Type	Seoul
Individual Box Width (Inch)	2.64		

3.54

0.39

