

#### Project:

Fixture Type:

Location:

Contact:

Wall mounted • Wet location listed PROGRESS LED

# energy sta

#### **Description:**

### Images:

The Leawood LED Collection small wall lantern provides delicate scrollwork with dramatic shadow patterns in a modern form. Intricate die cast aluminum construction in classic Black finish. A taller design accommodates the larger scale commonly seen in today's modern and traditional architecture.

#### **Specifications:**

- Black (-031) (painted)
- · Die-cast aluminum Construction
- LED Module is replaceable (part # 93074037)
- Intricate die cast aluminum construction
- · Delicate scrollwork with dramatic patterns in a taller design
- The medium wall lantern can be hung on either side of a front or rear door, by a garage, on exterior walls or in porches or outdoor living areas
- LED module hidden inside fixture so no visible light source seen
- Leawood's design and construction is a good fit for Traditional, Mediterranean and transitional homes
- Sturdy Black finish
- Measures 8in diameter x 13-5/8in ht.
- 9w LED module, 624 lumens 66 lumens/watt (source), 3000K color temperature, 90+ CRI.
- Progress Lighting products are designed for exceptional quality, reliability, and functionality
- · Includes installation instructions and mounting hardware
- Coordinating fixtures available
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting swivel mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR<sup>®</sup> qualified
- Meets California Title 24 JA8-2016

#### **Performance:**

| Number of Modules      | 1                                  |  |
|------------------------|------------------------------------|--|
| Input Power            | 9w                                 |  |
| Input Voltage          | 120 V                              |  |
| Input Frequency        | 60 Hz                              |  |
| Lumens/LPW (Source)    | 624/66 (LM-82)                     |  |
| Lumens/LPW (Delivered) | 409/43.9 (LM-79)                   |  |
| CCT                    | 3000 K                             |  |
| CRI                    | 90 CRI                             |  |
| Life (hours)           | 50,000 (L70/TM-21)                 |  |
| FCC                    | FCC Title 47, Part 15, Class B     |  |
| Min. Start Temp        | -30 °C                             |  |
| Max. Operating Temp    | 30°C                               |  |
| Warranty               | 5 year limited warranty            |  |
| Labels                 | cCSAus Wet location listed         |  |
|                        | ENERGY STAR <sup>®</sup> qualified |  |
|                        | Meets California Title 24 JA8-2016 |  |
|                        |                                    |  |



P560104-031-30

#### **Dimensions:**

Diameter: 8" Depth: 9-1/2" Height: 13-5/8" H/CTR: 4-5/8"



Wall mounted • Wet location listed PROGRESS LED

## P560104-031-30

nergy

#### **Dimming Notes:**

P560104 is designed to be compatible with many Triac/ELV controls.

The following is a partial list of known compatible dimmer controls.

#### **Dimming Controls**

| Lutron - NTEVL-300       |  |  |
|--------------------------|--|--|
| Lutron - DVELV-300P      |  |  |
| Lutron - Caseta Wireless |  |  |
| Leviton – 6672           |  |  |
| Leviton – 6674           |  |  |
| Lutron - AYCL-153P       |  |  |
| Lutron - AYLV-600P       |  |  |
| Lutron - MAELV-601       |  |  |
| Leviton - AWRMG-FAW      |  |  |

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.