

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## Disc Ceiling and Wall Mount

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
FM-304 4"	930 3000K - 90	12W	725	BN Brushed Nickel
FM-306 6"	940 4000K - 90	15W	945	BZ Bronze
FM-306-JB 6"			950	WT White

Example: **FM-304-930-BN**

### DESCRIPTION

Multiple high-powered LEDs illuminate an acrylic diffuser uniformly without socket shadows, which are common in conventional flush mounts. This multi-purpose Wet Location, Energy Star Rated flush mount can be mounted without a transformer on a ceiling or on a wall in a junction box, and also includes an optional retrofit kit with an A19 socket designed to fit into an existing 3" - 6" recessed unit. The disc is available in 6" and 4" sizes, and various finishes and color temperature options.

### FEATURES

- Multiple LED array for uniform illumination
- ACLED driverless technology
- 5 year warranty

### SPECIFICATIONS


<b>Construction:</b>	Die-cast aluminum with white acrylic diffuser
<b>Power:</b>	15W, 12W
<b>Input:</b>	120 VAC, 50/60Hz
<b>Dimming:</b>	ELV: 100-5%
<b>Light Source:</b>	Integrated LED
<b>Lens:</b>	Translucent acrylic diffuser
<b>Rated Life:</b>	50000 Hours
<b>Mounting:</b>	FM-306: Retrofit over a 5" or 6" recessed can or install over a 3" or 4" junction box, Can be mounted on ceiling or wall in all orientations, FM-306-930JB: Install over a 3" or 4" junction box, FM-304: Retrofit over a 4" recessed can or install over a 3" or 4" junction box
<b>Finish:</b>	Electrostatically Powder Coated White, Bronze, Electroplated Brushed Nickel
<b>Operating Temp:</b>	-4°F to 104°F (-20°C to 40°C)
<b>Standards:</b>	ETL, cETL, Wet Location Listed, Energy Star 2.0, Title 24 JA8-2016 Compliant, ADA

### REPLACEMENT PARTS

M2020-C-BK - N/A  
 M2020-C-GL - N/A  
 M2020-C-WT - N/A  
 M2015-C-BK - N/A  
 M2015-C-GL - N/A  
 M2015-C-WT - N/A  
 FM-306-RFK - 6" Retrofit Kit  
 FM-304-RFK - 4" Retrofit Kit



### FINISHES



### LINE DRAWING

