

Project:

Purolinear 360 LED Wall Bar Spec Sheet

SKU: 23QSCSR24R120PHA Learn more at: https://sonnemanlight.com/purolinear-360-led-wall-bar

Description: A system of linear tubes, set within the geometry of surfacemounted cylinder brackets, rotate individually to direct the LÉD illumination in 360 degrees along their axis. Arranged in a linear pattern or along a single path, the possibilities for compositions are endless and unlimited in scalability. Set on a wall, in line behind a bed, the rotatable luminaires provide the variability of direct or indirect illumination.

Type #:







Dimensions

Height: 48.75" Width: 24.75" Extends: 2.75" Minimum Extension: 2.75 Maximum Extension: 2.75 Canopy/Backplate/Base: Shape: Rectangle 24"/48" Size:

Electrical Specs

Bulb(s) Included?: Yes Integral LED Bulb 1 Type: **Bulb Quantity:** Input Voltage: 100-277VAC Wattage: 13 Initial Lumens: 3620 2590 **Delivered Lumens:** Color Temperature: 3000K CRI: 90 Power Supply Type: Driver Power Supply Quantity: Power Supply Location: Remote TRIAC/ELV/ 0-10V Dimming Type:

Installation

Installation: Licensed electrician required

Shade

Shade 1 Material: Optical Acrylic Shade 2 Material: Optical Acrylic

Available Finishes

Available Finishes: Polished Chrome (.01), Satin Black (.25), Satin Chrome (.23), Satin White (.03)

General Listings

Features:

Certification: Color/Finish:

Dark Sky Friendly:

ADA Compliant, Damp Rated C-ETL-US Satin Chrome (.23)