



**15205 MST**

**15205 BKT**

**15205 AZT**

Versatile, louvered 75-W. Max. fixture with multiple mounting options for deck or path lighting, on post, stem or bollard.

## SPECIFICATIONS

**Housing** Durable die-cast aluminum construction. Molded ribbed diffuser of clear UV stabilized high impact resistant polycarbonate.

*Mounting stems and bollard kits sold separately.*

**Finish** Textured Architectural Bronze, Textured Black, Textured Midnight Spruce™

**Wiring** 30" of usable 105°C 18 AWG wire leads. 120-Volt, medium base porcelain socket with nickel plated screw shell.

**Lamp Type** 75-W. Max. A19 light bulb (not supplied)

### Optional Mounting Accessories

15656, 15657 or 15658 – Stems

15276 – Power Post®

15665, 15666 or 15667 – Bollard Mounting Kits

15578 – Bollard Mounting Stakes

15671 – Bollard Template Kit

15601 – Surface Mounting Flange

(for attachment to junction box, not included)

15602 – Flange Mounting Nipple

U.S. Patent No. Des. 330,603

Canada Patent No. 69176

Korea Design Registration


Number 126685



Mounting stems



Base/deck mount



15205



Bollard kits

Footcandles/Distance from Fixture Center

Stem Height	1'	2'	3'	4'	5'	6'	7'	8'	9'
12"	10.1	7.7	1.7	.82	.48	.21	.11	-	-
*18"	4.9	4.7	2.8	1.0	.48	.27	.14	.07	-
24"	3.2	3.5	3.4	1.3	.62	.38	.21	.14	.07