

RGR series

When choosing a recessed fixture, eliminating glare is a priority. The unique positioning of the LED module in this series of downlights will meet that important need.

UPGRADE



WET



LOW-GLARE



ENERGY STAR



IC RATED




AIR TIGHT



JA8 CERTIFIED



Intertek



Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
RGR2-CC	2"	8 W	600 lm	750 lm	90	2700, 3000, 3500, 4000, 5000 K	120 V
RGR4-CC	4"	14 W	1100 lm	1200 lm			120 V
RGR4-CC-V-WH*	4"	14, 15 W	1100 lm	1200 lm			120, 277 V
RGR6-CC	6"	20 W	1600 lm	1900 lm			120 V

* 0-10V dimming, white finish only

Specifications

Every fixture includes a junction box with integrated dimmable driver
 Can be daisy chained (4" and 6" models only)
 Superior LED performance and lifespan
 Regressed light source
 Minimal heat emission
 Aluminum construction
 Switch-selectable CCT: 2700K/3000 K/3500 K/4000 K/5000 K
 IC certification (suitable for direct contact with insulation)
 Air-tight certified as per ASTM E283-04
 40° beam angle
 Suitable for wet locations
 JA8 Certified
 Ideal operating temperature: -20° to 40° C
 5-year warranty

Finish

- **BK** Black
- **SN** Satin Nickel
- **WH** White

Accessories

- RFP-23**
Rough-in plate for RGR2
- RFP-46**
Rough-in plate for RGR4 and RGR6

Note

Other color °T, finishes, and voltage options are available but may require MOQ's and longer lead times. Please contact your DALI representative for more information.

