

# WAC LIGHTING

## Paloma LED523 24W W Track Luminaire

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

| System Type & Voltage | Model  | Color Temp & CRI | Lumens | CBCP | Finish      |
|-----------------------|--------|------------------|--------|------|-------------|
| WTK-120 VAC           | LED523 | 27 2700K - 85    | 1340   | 6840 | BK Black    |
| WHK-277 VAC           |        | 30 3000K - 85    | 1500   | 7595 | PT Platinum |
|                       |        | 35 3500K - 85    | 1495   | 7280 | WT White    |
|                       |        | 40 4000K - 85    | 1600   | 7650 |             |
|                       |        | 927 2700K - 90   | 1260   | 6515 |             |
|                       |        | 930 3000K - 90   | 1350   | 6635 |             |

Example: **WHK-LED523-27-BK**

### DESCRIPTION

Museum-quality LED luminaire with adjustable beam angle. Designed for use on W track systems (120V, 277V).

### FEATURES

- Twist to adjust beam angle between 15° - 60°
- 365° horizontal rotation and 180° vertical aiming
- Driver hidden inside W track
- Integral selector to choose between independently controllable track circuits
- Comparable to 20W HID
- Driver concealed within the fixture
- 5 year warranty

### SPECIFICATIONS

|                        |   |
|------------------------|---|
| <b>Construction:</b>   | Die-cast aluminum with cap ring.                          |
| <b>Power:</b>          | 24W   |
| <b>Input:</b>          | 120 VAC, 277 VAC, 50/60Hz                                 |
| <b>Dimming:</b>        | ELV: 100-10%  |
| <b>Light Source:</b>   | Integrated LED<br>3 Step Mac Adam Ellipse                 |
| <b>Rated Life:</b>     | 50000 Hours   |
| <b>Finish:</b>         | Electrostatically Powder Coated White,<br>Platinum, Black |
| <b>Operating Temp:</b> | -4°F to 104°F (-20°C to 40°C)                             |
| <b>Standards:</b>      | ETL, cETL, Dry Location Listed                            |



### FINISHES



### LINE DRAWING

