Oslo Ceiling Fan

Back to Content page

120v: **3-101-xx**



FIXTURE TYPE		LOCATION		
PROJECT		DATE		
		-6 White	-20 Polished Nickel	-22 Oiled Bronze
-24 Satin Nickel with Option				
-24 Satin Nickel w	vith Optional LED Light kit	Without light kit	Without light kit	Without light kit
OPTIONAL LIGHT	vith Optional LED Light kit Optional LED Light kit 18W, 3000K, Dimmable LED with Matte White Gla	90CRI,	DIMENSIONS Dia.: 52.00″	
OPTIONAL LIGHT SOURCE	Optional LED Light kit 18W, 3000K,	90CRI, ss diffuser Blade-Pitch	DIMENSIONS Dia.: 52.00″	Without light kit
-24 Satin Nickel w OPTIONAL LIGHT SOURCE SPECIFICATIONS	Optional LED Light kit 18W, 3000K, Dimmable LED with Matte White Gla 4 Blades / 52" Blade Sweep / 14° 4" and 6" downrod (Included) Optional downrods available for higl 3 Speeds - Reversible 0.54A on high / 0.28A on low 64W on high / 16W on low 147 rpm on high / 72 rpm on low Wall control (Included)	90CRI, ss diffuser Blade-Pitch	DIMENSIONS Dia.: 52.00″	
OPTIONAL LIGHT SOURCE SPECIFICATIONS	Optional LED Light kit 18W, 3000K, Dimmable LED with Matte White Gla 4 Blades / 52" Blade Sweep / 14° 4" and 6" downrod (Included) Optional downrods available for hig 3 Speeds - Reversible 0.54A on high / 0.28A on low 64W on high / 16W on low 147 rpm on high / 72 rpm on low Wall control (Included) Remote control (Optional)	90CRI, ss diffuser Blade-Pitch h ceilings	DIMENSIONS Dia.: 52.00″	
OPTIONAL LIGHT SOURCE SPECIFICATIONS INPUT VOLTAGE ENERGY	Optional LED Light kit 18W, 3000K, Dimmable LED with Matte White Gla 4 Blades / 52" Blade Sweep / 14° 4" and 6" downrod (Included) Optional downrods available for hig 3 Speeds - Reversible 0.54A on high / 0.28A on low 64W on high / 16W on low 147 rpm on high / 72 rpm on low Wall control (Included) Remote control (Optional) 120V Airflow 4991 CFM at high speed 64 W at high speed	90CRI, ss diffuser Blade-Pitch h ceilings	DIMENSIONS Dia.: 52.00″	

