

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Dice Ceiling and Wall Mount

Model & Size	Color Temp & CRI	Watt	LED Lumens	Delivered Lumens	Finish
FM-4014 14"	2700K 90 3000K 90 3500K	31W 31W	1323 1356	610 640	BN Brushed Nickel

Example: **FM-4014-27-BN**

- For 277V special order, add an "F" before the finish: FM-4014F-27-BN
- For alternate color temperature, special order adding -27 or -30 or -35: FM-4014F-27-BN

DESCRIPTION

Thick-walled glass is uniformly illuminated in a design made for LED technology in a rectangular format. Full range dimming control. Mounts as robust ceiling luminaire or a compelling wall sconce.

FEATURES

- Etched 3/4" thick pressed glass diffuser with interior ceramic glaze
- Transformer installed within the Junction Box, transformer dimension: 2.00" x 1.38" x 1.02"
- 5 year warranty

SPECIFICATIONS

Color Temp:	3500K, 3000K, 2700K
Input:	120 VAC, 277 VAC, 50/60Hz
CRI:	90
Rated Life:	50000 Hours
Mounting:	Heavy gauge retention clips support trim firmly. Safety cabling standard., Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL
Construction:	Durable steel body with thick opal glass
Dimming:	ELV: 100 - 10% Damp Location Listed




FINISHES



Brushed Nickel

LINE DRAWING



4014