

Colton LED Outdoor Sconce CLTW Series

Features

Simplistic design. Down light with wall wash effect. Ideal use in entrances or anywhere general outdoor lighting is needed. Provides lighting in residential, commercial and hospitality applications. Meets ADA requirements. Fixture mounts to standard junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

All metal parts are powder coated in white or black.

Diffuser

Frosted white glass bottom diffuser.

Electrical

This unit is direct wired with a low voltage electronic LED driver. The constant current LED driver is rated for 120-277 VAC input, Minimum starting temp -20°F. LED driver is dimmable 0-10V DC.

Lamping

Fixture includes a LED modules capable of producing: 12W, 1000 source lumens. 3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for wet locations. ADA


Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.

LOCATION PREPARED BY COMMENTS CATALOG NUMBER DATE QUANTITY FIXTURE TYPE





Ordering Information:

White	Black	LED	Lumens	CCT	Н	W	D
CLTW060410L30D2WH	CLTW060410L30D2BK	12W	1000	3000K	4-1/4"	6-1/2"	2-1/2"

Source