

INSTALLATION INSTRUCTIONS

Item#749-2-XX-L

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

READ AND SAVE THESE INSTRUCTIONS

PREPARATION

1. Shut off power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts in a clean area. Take care not to misplace any small parts necessary for installation.

INSTALLATION & ASSEMBLY (Fig.1 & Fig.2)

3. Attach mounting plate (B) to outlet box (A) (not included) using slotted holes on mounting plate (B) and outlet box screws (C) provided. Making sure flat side of mounting plate (B) must face out.
4. Attach support cable (F) to slotted holes on mounting plate (B), and carefully allow support cable (F) to support the weight of fixture while wiring.
5. Pull power supply wires out from outlet box. Connect black supply wire to fixture's black wire using wire nuts (D). Connect white supply wire to fixture's white wire using wire nuts (D). Connect fixture ground wire and supply ground wire together using wire nuts (D). Wrap all wire connections with electrical tape for a more secure connection.
6. Carefully tuck all wire connectors neatly into outlet box.
7. Place fixture over outlet box and install fixture to bracket by pressing the clips (E) on fixture to mounting plate (B).

Your installation is now complete. Return power and test the fixture.

Care and maintenance

Use a clean, soft cloth to wipe the surface of the fixture.

DO NOT use any cleaners with chemicals, solvents or harsh abrasives

Dimming: Dimmable with ELV and/or LED compatible wall dimmer switches.

