

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	

Storm LED Sconce STMS Series

Features

Dynamic cut metal faceplate offers unique lighting array. Indirect light with wall wash effect. Fixture mounts to standard junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Back plate and bands are finished in silver or black chrome.

Diffuser

Edge-lit acrylic diffuser.

Electrical

This unit is direct wired with a constand current LED driver rated for 120-277V VAC. 0-10V Dimmable.

Lamping

Fixture includes an LED module capable of producing: 14" - 13W = 800 source lumens 3000K (CCT) rated for 50,000 hrs., 90 CRI

Certification


All fixtures are cETLus listed for damp locations. ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.





Ordering Information:

			Source				
	Silver	LED	Lumens	ССТ	н	W	D
STMS061408L30D2BC	STMS061408L30D2SL	13W	800	3000K	14"	5-1/2"	2"