

FX-3584-1 INSTALLATION SHEET

IMPORTANT SAFETY INSTRUCTIONS:

* These instructions are provided for your safety. It is very important that they are read completely before beginning the installation of your fixture.

* DIRECT WIRE FIXTURES: WE STRONGLY RECOMMEND INSTALLATION BY A LICENSED ELECTRICIAN.

TO ASSEMBLE:

Shut off the main electrical supply at fuse box/circuit breaker.

Remove all parts from carton. Do not throw away any parts as shown.

1. Unscrew ring (8), ditch plastic ring (6), take down the glass (7) and ditch plastic (6).
2. Reinstall glass (7) to socket (10) and secure it with ring (8).
3. Adjust the wire to desired length and secure it with the "8" shaped plastic clip (1).
4. Put the wire (1) through the I bar (2).
5. Connect the green ground wire "⏏" to the supply wire, Cathode wire "N" in white to the supply wire, Anode wire "L" in black to the supply wire in the junction box as illustrated with wire nuts.
6. Affix I bar (2) to junction box using mounting screws (3).
7. Affix the canopy (4) by screw (5).
8. Install the bulb (9).

Turn on power and enjoy!!!

**Use 60 Watt Max type A BULB
(Bulb not included)**

To avoid risk of fire, do not exceed the recommended wattage.

WARNINGS:

Turn off power (unplug from the wall outlet) before replacing the bulb(s), making sure the bulb(s) have sufficient time to cool down.

Do not subject the lighting fixture to any shock while lit as shattering of bulbs may result.

CARE INSTRUCTIONS:

To clean, use a soft cloth only. DO NOT use any chemical or abrasive cleaners.

★ Keep this instruction for future reference

