

Edmund LED Outdoor Sconce EDDW Series

Features

This outdoor LED light is ideal for security and general lighting. Up illumination (1-Light) or Up/down-light illumination (2-Light) for outdoor or indoor residential, commercial, and hospitality applications. Fixture mounts to a standard junction box (not included).

Construction

Die-cast aluminum construction. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Black powder coated finish.

Diffuser

Solid acrylic diffuser.

Electrical

Input 120-277 VAC / 60 Hz. Minimum starting temp -4° F/ -20°C.

LED

Integrated LED modules capable of producing: 1-LIGHT - 13W = 1200 source lumens, 1036 delivered lumens 2-LIGHT - 25W = 2400 source lumens, 2043 delivered lumens Adjustable Choice 3000K, 3500K, 4000K (CCT). Rated for 50,000 Hrs., 90 CRI.


Certification

All fixtures are cETLus listed for wet locations. Title 24/JA8 Compliant (outdoor only).

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.



















Ordering Information:

			Delivered					
Black	LED	Lumens	Lumens	Adjustable CCT	Н	W	D	
EDDW0608LAJMVBK (1-LIGHT)	13W	1200	1036	3000K/3500K/4000K	8"	3-1/2"	6-1/4"	
EDDW0613LA IMVBK (2-LIGHT)	25\\/	2400	2043	3000K/3500K/4000K	11_7/9"	7_1/2"	6-1/4"	