

Watson LED Outdoor Sconce WTNW Series

Features

Simplistic design. Down light with wall wash effect. Ideal use in entrances or anywhere general outdoor lighting is needed. Provides lighting in residential, commercial and hospitality applications. Meets ADA requirements. Fixture mounts to standard junction box (not included).

Construction

Fabricated aluminum construction. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

All metal parts are powder coated in White or Black.

Diffuser

Frosted white glass bottom diffuser.

Electrical

Input 120-277 VAC / 60 Hz. 0-10V dimming Minimum starting temp -4° F/ -20°C.

Lamping

Integrated LED modules capable of producing: 12W = 1100 source lumens, 424 delivered lumens 3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for wet locations. ADA Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.

Ordering Information:

			Source	Delivered				
White	Black	LED	Lumens	Lumens	ССТ	H	W	D
WTNW0506L30D2WH	WTNW0506L30D2BK	12W	1100	424	3000K	6″	5″	3-1/2"

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	







