

Arden LED Sconce **RNS Series**

Features

Modern design featuring a walnut accent with a glass-in-glass diffuser. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Can be mounted up or down. Meets ADA requirements. Fixture mounts standard to junction box (not included).

Construction

Die-cast metal diffuser bracket, stamped metal backplate and hand-blown glass diffuser. Power supply connections must be made inside a junction box (not included).

Finish

Walnut accent, all cast metal components are finished in Satin Nickel or Oil-Rubbed Bronze.

Diffuser

Clear outer glass diffuser, white inner glass diffuser.

Electrical

Input 120 VAC, 60 Hz LED. Compatible with residential TRIAC and ELV dimmers.

LED

Integrated LED modules capable of producing: 15.5W = 1200 source lumens, 700 delivered lumens 3000K (CCT) rated for 50,000 hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations. ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.

DATE LOCATION PREPARED QUANTITY BY COMMENTS FIXTURE TYPE CATALOG NUMBER










Satin Nickel

Oil-Rubbed Bronze





Ordering Information:

| | | | | Delivered | | | | |
|-------------------|-------------------|-------|--------|-----------|-------|---------|--------|----|
| Satin Nickel | Oil-Rubbed Bronze | LED | Lumens | Lumens | ССТ | н | W | D |
| RNS5161200L30D1SN | RNS5161200L30D1RB | 15.5W | 1200 | 700 | 3000K | 15-3/4" | 4-3/4″ | 4″ |