UL SPECIFICATION

 * FIXTURE SHALL BE LISTED FOR LOCATION ONLY AND LABELED AS SUCH.
* FIXTURE MUST BE MANUFACTURED IN ACCORDANCE WITH UL STANDARD 1598.

PARTS SPECIFICATIONS ITEM QTY DESCRIPTION

- A (1) SOCKET- UL LISTED/CSA CERTIFIED BASE=MEDIUM SOCKET=PORCELIN SEE LEAD WIRE FOR SOCKET WIRE SPEC.
- B (1) LEAD WIRE- 8" FROM CANOPY UL LISTED/CSA CERTIFIED, AWG #18 150°C BLACK AND WHITE WIRE. STRIP 1/2 [12.7], SPLIT 3 [76.2]. FROM TOP OF SCROLL. (SEE CHART FOR COLOR).
- C (1) GROUND WIRE- 8" FROM CANOPY 1/4 LAY COPPER GROUND WIRE. FROM TOP OF SCROLL. (SEE CHART FOR TINT).

INNOVATIONS LIGHTING <u>DESIGN COPYRIGHT - 11/12/2019</u> ALL RIGHTS RESERVED AND MAY NOT BE DUPLICATED WITHOUT OUR WRITTEN PERMISSION



UTICE: ANY DESIGN OR OTHER INFORMATION HEREON DEVELOPED BY THIS COMPANY CONFIDENTIAL MATERIAL AND EXCLUSIVE PROPERTY OF THE L.D. ALLYA CO. R REPRODUCTION REQUIRES THE WRITTEN CONSENT OF THE L.D. ALLYA CO.

INNOVATIONS CREATIVITY MEET." EVOLUTIONARY DE."IGNO

	DRAWN IN	"mm" DIMENSION INDICATED IN [] DIMENSION IN [] IS FOR REF. ONLY					TITLE		
		TOLERANCES (EXCEPT AS NOTED)					2LT WALL MOUNT		
		DECIMAL NONE ±.031 .X ±.015 .XX ±.010 .XXX ±.005	ANGULAR ± 1/2°	FRACTION ± 1/32		SCALE 1:3	PART NO. WALL		REV.
			DATE 3/31/2021	DRAWN BY SSL	СНЕСКЕД ВУ Х	APPROVED BY	ITEM NO. 34	12-2W-BK-CLW	REVA

