



15315 BKT



15315 AZT
15915 AZT6



15315 BE



15315 MST

SIDE MOUNT

Popular design in a side-mount fixture for more directional lighting without glare.

SPECIFICATIONS

Housing Durable die-cast aluminum construction

Finish Textured Architectural Bronze, Beach, Textured Black, Textured Midnight Spruce™

Wiring 35' of usable #18-2, SPT-1-W leads. Cable connector supplied with fixture. 12-Volt S-8 wedge socket.

Light Bulb 24.4-W. Max. 3156K (15598 CLR) (nominal at 12-Volts) supplied. Can also use 18.5-W. 3155K (15599CLR).

Mounting Accessories Included

18" stem* and 8" In-ground stake

Optional Mounting Accessories

15601 – Surface Mounting Flange

15607 – Tree/Surface Mounting Bracket

Optional Lens Accessories 15695 CLR – Lens

Bulk Pack 15315AZT6 includes 6 fixtures, 6 (8") in-ground stakes and 6 light bulbs

Bulk Pack Pre-Wired With Universal Connector


15915AZT6 with 25' of 16 guage cable lead for use with Pro Series LV Junction

U.S. Patent No. Des. 330,603

Canada Patent No. 69176

Korea Design Registration

Number 126685



Footcandles/Distance from Fixture Center

Stem Height	1'	2'	3'	4'	5'	6'	7'	8'	9'
12"	18.7	4.3	1.4	.27	-	-	-	-	-
*18"	15	5.2	1.8	.8	.27	.03	-	-	-
24"	11.6	5.1	2.2	.97	.48	.2	.07	-	-

Light Bulb Conversion: 18.5W, 3155K Light Bulb, FCx66