UL SPECIFICATION

* FIXTURE SHALL BE LISTED FOR LOCATION ONLY AND LABELED AS SUCH. * FIXTURE MUST BE MANUFACTURED IN ACCORDANCE WITH UL STANDARD 1598.

PARTS SPECIFICATIONS ITEM QTY DESCRIPTION

FRACTIONAL

± 1/32

DRAWN BY

SSL

SCALE

х

PART NO.

1:5

CKED B

Х

DECIMAL ANGULAR

± 1/2°

DATE

3/31/2021

NONE ±.031

.X ±.015 .XX ±.010 .XXX ±.005

DRAWN IN THIRD ANGLE

PROJECTION

 \oplus \oplus

- SOCKET- UL LISTED/CSA CERTIFIED А (1) BASE=MEDIUM SOCKET=PORCELIN SEE LEAD WIRE FOR SOCKET WIRE SPEC.
- LEAD WIRE- 8" FROM CANOPY В (1) UL LISTED/CSA CERTIFIED, AWG #18 105°C BLACK AND WHITE WIRE. STRIP 1/2 [12.7], SPLIT 3 [76.2]. FROM TOP OF SCROLL. (SEE CHART FOR COLOR).
- С (1) GROUND WIRE- 8" FROM CANOPY 1/4 LAY COPPER GROUND WIRE. FROM TOP OF SCROLL.

(SEE CHART FOR TINT).

INNOVATIONS LIGHTING DESIGN COPYRIGHT - 11/12/2019 ALL RIGHTS RESERVED AND MAY NOT BE DUPLICATED WITHOUT OUR WRITTEN PERMISSION



REV.

REV.A

	TTY MEET." EVOLUTIONARY DE."IGNO
"mm" DIMENSION INDICATED IN [] DIMENSION IN [] IS FOR REF. ONLY TITLE	
TOLERANCES (EXCEPT AS NOTED) 41 T	WALL MOUNT

WALL

ITEM NO. 342-4W-BK-CLW

