TIKI LED AREA LIGHT

6041/6042





Fixture Type:	
Catalog Number:	
Project:	
Location:	

PRODUCT DESCRIPTION

Sturdy side mount design works well in applications where directional illumination is desired

FEATURES

- IP66 rated, Protected against powerful water jets
- · Factory sealed water tight fixtures
- Solid diecast corrosion resistant aluminum alloy
- Recommended spacing for installation: Residential: 7 to 9ft; Commercial: 5 to 7ft
- Mounting stake, 6 foot lead wire, and direct burial gel filled wire nuts are included
- Maintains constant lumen output against voltage drop
- UL & cUL 1838 Listed

SPECIFICATIONS


Input: 9-15VAC (Transformer is required)

 Power:
 6.5W / 9.5VA

 Brightness:
 225 lm

 CRI†
 90+

 Rated Life:
 60,000 hours




ORDERING NUMBER

	Color Temp	Finish
6041 <i>Tiki</i>	27 2700K Warm White30 3000K Pure White	

6042-___BK

Example: 6042-30BK



TIKI LED AREA LIGHT 6041/6042



Surface Mount Flange/Stake



Includes three 7 inch threaded stainless steel stabilizing pins for ground mounting or surface mounts with four screws or over a junction box

Additional Mounting Stake



9000-ST9-BK *Durable PVC stake*

5000-SCP-BZBronze on Aluminum



Guardian Mount

Heavy duty stainless steel spike to position fixture. Formed from a single piece of metal

9000-SP9-BZ *Stainless Steel*

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS *75W Max*

9150-TRN-SS *150W Max*

9300-TRN-SS *300W Max*

9600-TRN-SS 600W Max

