SONNEMAN A WAY OF LIGHT

Project:


Thin-Line LED Pendant Spec Sheet

SKU: 2818.25-6-35 Learn more at: https://sonnemanlight.com/thin-line-led-pendant

Description:

A system of minimally scaled LED linear pendants, uplight/downlight wall bars, and indirect light wall bars, Thin-Line is offered in a variety of lengths, finishes, and lighting configurations. Thin-Line pendants are available in single- and double-sided configurations; the single-sided configurations can be installed as a downlight or up-light, providing direct or indirect illumination. Our <u>Optional Mini Box Canopy</u> is also available for the Thin-Line LED Pendant.

Type #:



Licensed

required

5.75["] 73.75"

electrician

Compatible

75" X 7" X 4"

Aluminum

w/Optical

Acrylic

8 LBS

Dimensions

Height:	5"	Insta
Width:	72"	
Length:	0.75"	
Canopy/Backplate/Base:	4.5"	Slop
Size:	6' Two-Sided	Minir

Yes

2

72

90

2

4440

2700

3500K

Driver

Remote TRIAC/ELV

Integral LED

120VAC

Electrical Specs

Bulb(s) Included?: Bulb 1 Type: Bulb Quantity: Input Voltage: Wattage: Initial Lumens: Delivered Lumens: Color Temperature: CRI: Power Supply Type: Power Supply Quantity: Power Supply Location: Dimming Type: Installation Installation:

> Sloped Ceiling Compatible?: Minimum Hanging Height: Maximum Hanging Height:

Shipping

Carton 1 L x W x H: Carton 1 Gross Weight:

Shade

Shade 1 Material:

Available Finishes

Available Finishes: Bright Satin Aluminum (.16), Satin Black (.25), Satin White (.03)

General Listings

Features: Certification: Color/Finish: Damp Rated C-ETL-US Satin Black (.25)