



Project:

ALC LED Sconce Spec Sheet

SKU: 3050.13-SN25 Learn more at:
<https://sonnemanlight.com/alc-led-pendant>

Description: A classic modern architectural lighting form, Architectural Lighting Cylinders are available in a **surface mount** configuration as well as a **sconce** and pendant in a variety of sizes and finishes, with multiple beam spread options and a number of glass and metal trims.

Type #:



Dimensions

Height:	8.25"
Extends:	3.5"
Minimum Extension:	3.5
Maximum Extension:	3.5
Diameter:	2"
Canopy/Backplate/Base:	4.5"
Shape:	Snoot Trim
Size:	2" One-Sided
Canopy/Backplate/Base Depth:	0.5

Installation

Installation:	Licensed electrician required
Installation Orientation:	Any Orientation

Shade

Lens Type:	25 Narrow Flood Lens
Shade 1 Material:	Aluminum

General Listings

Features:	Damp Rated
Certification:	C-ETL-US
Color/Finish:	Satin Nickel (.13)
Dark Sky Friendly:	N

Electrical Specs

Bulb(s) Included?:	Yes
Bulb 1 Type:	Integral LED
Bulb Quantity:	1
Input Voltage:	120VAC
Wattage:	10
Initial Lumens:	1060
Delivered Lumens:	800
Color Temperature:	3000K
CRI:	90
Power Supply Type:	Driver
Power Supply Quantity:	1
Power Supply Location:	Outlet Box
Dimming Type:	TRIAC/ELV
Bulb Max Wattage:	10

Available Finishes

Available Finishes: Satin Nickel w/Bezel Trim, Satin Nickel w/Etched Glass Trim, Satin Nickel w/Etched Ribbon Glass Trim, Satin Nickel w/Snoot Trim