

Project:

# Thin-Line LED Wall Bar Spec Sheet

SKU: 2810.25-8 Learn more at: https://sonnemanlight.com/thin-line-led-wall-bar

Description:

A system of minimally scaled LED uplight/downlight wall bars, indirect light wall bars, and pendants, Thin-Line is offered in a variety of lengths, finishes, and lighting configurations. One-sided configurations direct light in a single direction, and can be mounted in an uplight or downlight orientation. Two-sided configurations direct light both up and down.

Type #:

### Dimensions

Height:	1"
Width:	96"
Extends:	3.5"
Minimum Extension:	3.5"
Maximum Extension:	3.5"
Size:	8' One-Sided
Canopy/Backplate/Base Width:	1
Canopy/Backplate/Base Height:	1

### **Electrical Specs**

Bulb(s) Included?:
Bulb 1 Type:
Bulb Quantity:
Input Voltage:
Wattage:
Initial Lumens:
Delivered Lumens:
Color Temperature:
CRI:
Power Supply Type:
Power Supply Quantity:
Power Supply Location:
Dimming Type:
Bulb Max Wattage:

Yes Integral LED 1 120VAC 47 3120 1800 3000K 90 Driver 1 Remote TRIAC/ELV 47

### Installation

Installation:

Installation Orientation:

## Shipping

Carton 1 L x W x H: Carton 1 Gross Weight:

#### Shade

Shade 1 Material:

Aluminum w/Optical Acrylic

Licensed

electrician

Orientation

99" X 7" X 4"

6 LBS

required

Any

### **Available Finishes**

Available Finishes: Bright Satin Aluminum (.16), Satin Black (.25), Satin White (.03)

#### **General Listings**

Features: Certification: Color/Finish:

Dark Sky Friendly:

Damp Rated C-ETL-US Satin Black (.25) N