

# LUNA Pendant

120v : **3-670-xx**  
277v: **37-670-xx**

# oxygen

FIXTURE TYPE \_\_\_\_\_ LOCATION \_\_\_\_\_

PROJECT \_\_\_\_\_ DATE \_\_\_\_\_




-22 Oiled Bronze

-20 Polished Nickel

-24 Satin Nickel

-40 Aged Brass

- LIGHT SOURCE** 1 x 5.12W LED, 3000K, CRI 90
- LUMINAIRE POWER** 6.56W at 120V
- RATED LIFE** 60000 hr RL
- OPTIONAL COLOR TEMPERATURES** 2700K, 3500K, 4000K
- LUMEN OUTPUT** Delivered: 368 lm (LM-79)
- INPUT VOLTAGE** 120V or 277V
- DRIVER OUTPUT** 150 mA, 6W
- DIMMING** 0-10v & Phase (ELV) Dimming  
50/60Hz 100% to 10% Dimming
- CONSTRUCTION** Plated Steel and Glass
- DIFFUSER** - White Opal Glass
- FINISHES** Polished Nickel (-20), Oiled Bronze (-22), Satin Nickel (-24), Aged Brass (-40)
- MOUNTING** 4" Octagonal J-Box, 2"x 3" J-Box
- STANDARDS** ETL Dry/Damp listed, ADA compliant, Conforms to UL STD 1598, Certified CAN/CSA, STD C22.2 No 250.0.



**DIMENSIONS**  
**Dia. Canopy: 5.88"**  
**W. Fixture: 6.00"**  
**H. Fixture: 6.75"**  
**Supplied with 8 ft braided cord**

Order example for standard fixture:  
**3-670-24** (x- Voltage - xxx-Sequence # - xx-Finish)  
3: 120v, 37: 277v  
Order example for optional color temperatures: **3-670-2724**  
27: 2700K, 35: 3500K, 40: 4000K

