



KONA

VANITIES WALL



SPECIFICATIONS:

DESCRIPTION

2-4 light vanity luminaires featuring handcrafted glass.

LAMPING

Standard: 40W Low-pressure G9 Halogen 120V lamp, included. Suitable for use in an open fixture. Dimmable with standard incandescent dimmer.

LED: 5W LED Replaceable source 120V, dimmable, included.

DIFFUSER

Shade shall be handcrafted glass of various decors. 5.5" Dia. x 2.5" H, spaced 7.875" apart on center.

CONSTRUCTION

Fixture utilizes metal arm assembly and stamped steel body, with plated finish. Decorative finials can be removed for downlighting applications. Decorative outlet box cover optional when not required.

METAL FINISH

Fixture shall be finished in Bronze, Chrome or Satin Nickel.

MOUNTING

Installs directly to a 4" octagonal outlet box, with 1.75" left or right offset. Canopy allows direct wiring without outlet box, where armored cable or non-metallic sheathed cable is employed, and the decorative outlet box cover is not required. Orient upward or downward, wall-mount only.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



KONA SHOWN IN WHITE STARPOINT (282453) WITH SQUARE CANOPY

550493
DICRO SWIRL

117687
BLUE MATTE

117652
MARBLE




117691
BI-COLOR

117681
SUNSET

282453
WHITE STARPOINT

282890
MANGO STARPOINT

282484
BLUE STARPOINT



For ordering information, see next page

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 7/15



KONA


VANITIES WALL

ORDERING:

FIXTURE	GLASS OPTIONS	METAL FINISH	METAL FINISH	OPTIONS
2SW 2 Light Vanity	117607 White	(blank) 40W G9 Hal	BR Bronze	SQ Square Canopy
3SW 3 Light Vanity	117652 Marble	LED 5W LED 120V, dimmable	CR Chrome	
4SW 4 Light Vanity	117681 Sunset		SN Satin Nickel	
	117687 Blue Matte			
	117691 Bi-color			
	282453 White Starpoint			
	282484 Blue Starpoint			
	282490 Mango Starpoint			
	550493 Dicro Swirl			

Ex. 3SW-550493-SN

Kona 3-Light Vanity w/ Dicro Swirl Glass, Satin Nickel Finish




2SW: 14.625" L



3SW: 22.5" L



4SW: 30.375" L



Canopy allows direct wiring without outlet box, where armored cable or non-metallic sheathed cable is employed, and the decorative outlet box cover is not required. Orient upward or downward, wall-mount only.

LED SCONCES:

- Total power of only 5 watts
- Dimmable with a standard dimmer
- Rated life: 25,000 hours
- 450 lumens
- CCT: 3000° Kelvin
- CRI: 80+

Project Information: