

## 60" Gaze Fan

 Ceiling mounted • Dry location listed 

### Description:

Relax under a refreshing breeze created by this stylish, yet efficiently functional, Gaze ceiling fan featuring a cutting-edge LED light source. With a soft, opal white light shade, extending, distressed Ebony blades, and a Black-finish center, this ceiling fan will keep you cool as you unwind in your living room or bedroom at the end of a warm day.

### Specifications:

- Black (-31) (painted)
- Steel Construction
- White Opal polycarbonate lens
- Stylish, yet efficiently functional, oversized ceiling fan ideal for keeping you cool as you relax in a great room, living room, bedroom, or bonus room
- Designed with a simple, Black-finish center from which extends three, 60-in, distressed Ebony or Matte Black reversible plywood blades responsible for creating a refreshing air flow
- Effortlessly adjust the full range dimming and fan speed settings with the accompanying remote control with its batteries already included, making it ready for immediate use
- An opal white, shatter-proof shade covers a cutting-edge LED light source that emits soft, gentle light while providing you with energy- and cost-saving benefits
- The clean, simple design makes the fan a perfect addition to Modern or Urban Traditional settings
- Measures 60 in X 13-1/8 in ht with 80 in lead wires and includes a 3/4 in X 6 in down rod with the ability to order longer accessory rods separately
- UL dry location listed and can be used to comply with California Title 20 or to comply with 2016 Title 24 JA8
- Light kit includes an 18w dimmable, 3000K LED module that offers a 1400 lumens source, 90+ CRI
- Mounting hardware included
- Limited lifetime warranty included
- Dimmable to 10% brightness (See Dimming Notes) canopy covers a standard 4" octagonal recessed outlet box
- Mounting Yes for outlet box included
- 80" of wire supplied
- Meets California Title 24 JA8-2016

### Performance:

|                     |  |
|---------------------|--|
| Number of Modules   | 1  |
| Input Power         | 18w  |
| Input Voltage       | 120 V  |
| Input Frequency     | 60 Hz  |
| Lumens/LPW (Source) | 1400/77.7 (LM-82)  |
| CCT                 | 3000 K   |
| CRI                 | 90+ CRI  |
| FCC                 | FCC Title 47, Part 15, Class B                               |
| Min. Start Temp     | -10 °C   |
| Max. Operating Temp | 30 °C  |
| Warranty            | Limited Lifetime warranty                                    |
| Labels              | UL Dry location listed<br>Meets California Title 24 JA8-2016 |

## P2554-3130K

### Images:



### Dimensions:

Diameter: 60"  
Length: 60"  
Height: 13-1/8"

**P2554-3130K****Dimming Notes:**

---

P2554 is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

**Dimming Controls**

---

Lutron - NTEVL-300

Lutron - DVELV-300P

Lutron-DVCL-253P

Lutron - Caseta Wireless

IDevices - IDEV009

Leviton – 6672

Leviton – 6674

Lutron - AYCL-153P

Lutron - TGCL-153-PH-WH

Lutron - AYLV-600P

Lutron - MAELV-601

Leviton -AWSMT-EAW

Lutron - N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.