

Project:

## ALC LED Sconce Spec Sheet

SKU: 3051.13-GN25-GN25    Learn more at:  
<https://sonnemanlight.com/alc-led-pendant>

Description: A classic modern architectural lighting form, Architectural Lighting Cylinders are available in a [surface mount](#) configuration as well as a [sconce](#) and pendant in a variety of sizes and finishes, with multiple beam spread options and a number of glass and metal trims.

Type #:



### Dimensions

Height:	8.5"
Extends:	3.5"
Minimum Extension:	3.5
Maximum Extension:	3.5
Diameter:	2"
Canopy/Backplate/Base:	4.5"
Shape:	Etched Glass Trim
Size:	2" Two-Sided
Canopy/Backplate/Base Depth:	0.5

### Installation

Installation:	Licensed electrician required
Installation Orientation:	Any Orientation

### Shade

Lens Type:	25 Narrow Flood Lens
Shade 1 Material:	Etched Glass

### General Listings

Features:	ADA Compliant, Damp Rated
Certification:	C-ETL-US
Color/Finish:	Satin Nickel (.13)
Dark Sky Friendly:	N

### Electrical Specs

Bulb(s) Included?:	Yes
Bulb 1 Type:	Integral LED
Bulb Quantity:	2
Input Voltage:	120VAC
Wattage:	20
Initial Lumens:	2120
Delivered Lumens:	1600
Color Temperature:	3000K
CRI:	90
Power Supply Type:	Driver
Power Supply Quantity:	1
Power Supply Location:	Outlet Box
Dimming Type:	TRIAC/ELV
Bulb Max Wattage:	20

### Available Finishes

Available Finishes: Satin Nickel w/Bezel Trim, Satin Nickel w/Etched Glass Trim, Satin Nickel w/Etched Ribbon Glass Trim, Satin Nickel w/Snoot Trim