

UNDERCABINET RESIDENTIAL & COMMERCIAL



LED LINKABLE UNDERCABINET WITH SWITCHABLE CCT

The SG150 is a shallow profile undercabinet fixture, measuring merely 1". With an on/off and three-way color temperature switch built into the fixture, the user can select between a warmer 2700K tone, a natural 3000K or 4000K light outputs with perfect diffusion. Fixtures are dimmable with most common TRIAC or ELV Dimmers. Linkable up to 200W max with Direct Connectors (SG-DC) or Connecting Cables (SG-CC) of various lengths. Fixtures can be hardwired using the Hardwire Box with built-in switch (SG150-WB), or plugged directly into a standard wall outlet with a Cord and Plug (SG-PC). Mounts easily with included captive screws. Fixtures are equipped with (1) SG-DC Direct Connector and (1) SG150-KOC Knock Out Clamp.



On/Off and 3-way 2700K/3000K/4000K switches

SG150

LED LINKABLE UNDERCABINET WITH SWITCHABLE CCT



Dims: 3 5/8" W x 1" H

Max Run: 200W

Housing: Powder-coated Aluminum

Dimming: TRIAC, ELV

Includes: (1) SG-DC, (1) SG150-KOC

TO ORDER

MODEL	LENGTH	CCT	FINISH
SG150	-	SWC	WH
	08 - 8"	SWC - Switchable	WH - White
	16 - 16"	27K/30K/40K	
	24 - 24"		
	32 - 32"		

MODEL	WATTAGE	CCT	LUMEN	EFFICACY
SG150-08	6W	2700K	400 Lm	67 Lm/W
		3000K	420 Lm	70 Lm/W
		4000K	415 Lm	69 Lm/W
SG150-16	10W	2700K	850 Lm	85 Lm/W
		3000K	870 Lm	87 Lm/W
		4000K	865 Lm	87 Lm/W
SG150-24	14W	2700K	1000 Lm	71 Lm/W
		3000K	1030 Lm	74 Lm/W
		4000K	1020 Lm	73 Lm/W
SG150-32	16W	2700K	1150 Lm	72 Lm/W
		3000K	1200 Lm	75 Lm/W
		4000K	1180 Lm	74 Lm/W

Additional power supply cables, connecting cables, hard-wire boxes sold separately. Specifications subject to change without notice. See spec sheet or jescolighting.com for more details.

ACCESSORIES & COMPONENTS



SG-DC
Direct Connector
(1) included with each fixture



SG150-KOC
Knockout Clamp
(1) included with each fixture



SG-PC24-W
SG-PC72-W
SG-PC96-W
SG-PC144-W
Power Cords
Length: 2', 6', 8' & 12'



SG-PCL
6' Right Angle Power Cord & Plug from back
SG-PCLL
6' Right Angle Power Cord & Plug from front



SG-CC6
SG-CC12
SG-CC24
SG-CC36
Connecting Cable
Length: 6", 12", 24", 36"



SG-CC6L
SG-CC12L
SG-CC24L
SG-CC36L
Right Angle Connecting Cable
Length: 6", 12", 24", 36"



SG150-WB
Wiring Box with Switch
6 1/4" L x 3 5/8" W x 1" H
Finish: White

LED LINKABLE RIGID LINEAR WITH SWITCHABLE CCT



The SG250 is a direct replacement for existing fluorescent fixtures with the same low profile and minimal footprint. Built-in three-way color temperature switch provides options of 2700K, 3000K and 4000K. Dimmable using most common TRIAC or ELV Dimmers. Linkable up to 10 fixtures with Direct Connectors (SG-DC) or Connecting Cables (SG-CC) of various lengths. Fixtures may be hardwired using a Hardwire Box (SG-B, SG-BM) or plugged directly into a standard wall outlet with a Cord and Plug (SG-PC). Fixtures are equipped with (1) SG-DC Direct Connector, (2) SG250-MC Vertical Mounting Clips.

SG250

LED LINKABLE RIGID LINEAR WITH SWITCHABLE CCT



Dims: 1" W x 1 5/16" H
Max Run: 10 fixtures
Dimming: TRIAC, ELV
Includes: (1) SG-DC, (2) SG250-MC

TO ORDER


MODEL	LENGTH	CCT	FINISH
SG250	-	-	-
	08 - 9" 12 - 11" 24 - 24" 36 - 36" 48 - 48" 60 - 58"	SWC - Switchable 27K/30K/40K	WH - White

MODEL	WATTAGE	CCT	LUMEN	EFFICACY
SG250-08	4W	2700K	270 Lm	68 Lm/W
		3000K	280 Lm	70 Lm/W
		4000K	270 Lm	68 Lm/W
SG250-12	5W	2700K	410 Lm	82 Lm/W
		3000K	420 Lm	84 Lm/W
		4000K	410 Lm	82 Lm/W
SG250-24	9W	2700K	690 Lm	77 Lm/W
		3000K	700 Lm	78 Lm/W
		4000K	690 Lm	77 Lm/W
SG250-36	12W	2700K	890 Lm	74 Lm/W
		3000K	900 Lm	75 Lm/W
		4000K	890 Lm	74 Lm/W
SG250-48	17W	2700K	1240 Lm	73 Lm/W
		3000K	1250 Lm	74 Lm/W
		4000K	1240 Lm	73 Lm/W
SG250-60	22W	2700K	1880 Lm	85 Lm/W
		3000K	1900 Lm	86 Lm/W
		4000K	1880 Lm	85 Lm/W

Additional power supply cables, connecting cables, hard-wire boxes sold separately. Specifications subject to change without notice. See spec sheet or jescolighting.com for more details.

ACCESSORIES & COMPONENTS

<p>SG-DC Direct Connector (1) included with each fixture</p>	<p>SG250-MC Mounting Clip 0° vertical mount. (2) included with each fixture</p>	<p>SG-PC24-W SG-PC72-W SG-PC96-W SG-PC144-W Power Cords Length: 2', 6', 8' & 12'</p>	<p>SG-PCL 6' Right Angle Power Cord & Plug from back SG-PCLL 6' Right Angle Power Cord & Plug from front</p>
<p>SG-CC6 SG-CC12 SG-CC24 SG-CC36 Connecting Cable Length: 6', 12", 24", 36"</p>	<p>SG-CC6L SG-CC12L SG-CC24L SG-CC36L Right Angle Connecting Cable Length: 6', 12", 24", 36"</p>	<p>SG-BM SG-BM-SW SG-B Wiring Boxes</p>	



For more details and product specifications please visit JESCOLIGHTING.COM



**NEW YORK
CORPORATE OFFICE**

15 Harbor Park Drive
Port Washington NY 11050
TEL 800 527 7796
FAX 855 265 5768

LOS ANGELES

219 South 6th Avenue
City Of Industry CA 91746
TEL 800 527 7796
TEL 626 333 3661
FAX 626 333 2955

JESCOLIGHTING.COM
info@jescolighting.com

© 2022 JESCO LIGHTING

LCAT-SG150/250

